## Product data sheet Characteristics

## 9007AO1

# Snap basic limit switch, 9007, 600 VAC 15amp ao +options



Main	
Range of product	9007
Series name	Heavy duty
Product or component type	Snap basic limit switch
Device short name	9007AO/CO
Body type	Fixed

#### Complementary

Mounting mode	-	
Operator profile	Plunger head	
Material	Metal	
Body material	Cast zinc	
Operator material	Cast zinc	
Fixing mode	By the body	
Movement of operating head	Linear	
Type of operator	Spring return plunger plastic with thermoplastic end	
Switch actuation	On end	
Type of approach	Vertical approach, 1 direction	
Electrical connection	12 cables for 6 binder head screw terminals (AWG 22AWG 14)	
Number of poles	1	
Contacts type and composition	NC-NO, switch function: SPDT-DB	
Contact form	Form Z	
Contact operation	Snap action	
Number of steps	1	
Contacts material	Silver contacts	
Positive opening	Without	
Terminals description ISO n°1	(1-2)NC	
Minimum force for tripping	0.44 lbf	
Maximum force for tripping	0.69 lbf	
[le] rated operational current	5 A at 600 V AC, A600 conforming to NEMA rating designation 6 A at 480 V AC, A600 conforming to NEMA rating designation 10 A at 240 V AC, A600 conforming to NEMA rating designation 15 A at 120 V AC, A600 conforming to NEMA rating designation 0.1 A at 250 V DC 0.25 A at 125 V DC	
[Ithe] conventional enclosed thermal current	15 A	
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to UL 508 for contact block 600 V conforming to CSA C22.2 No 14 for contact block	
Width	21.08 mm	
Height	63.5 mm	
Depth	26.16 mm	
Net weight	0.05 kg	

#### Environment

NEMA degree of protection	NEMA 1 conforming to Nema type 250
IP degree of protection	IP20 conforming to IEC 60529
Ambient air temperature for operation	-20185 °F
Ambient air temperature for storage	-20185 °F

## Packing Units

· coming or mo	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.3 cm
Package 1 Width	10.2 cm
Package 1 Length	15.2 cm
Package 1 Weight	40.8 g
Unit Type of Package 2	CAR
Number of Units in Package 2	100
Package 2 Height	13.208 cm
Package 2 Width	24.638 cm
Package 2 Length	27.94 cm
Package 2 Weight	4.205 kg
Unit Type of Package 3	PAL
Number of Units in Package 3	2000
Package 3 Height	101.6 cm
Package 3 Width	101.6 cm
Package 3 Length	121.92 cm
Package 3 Weight	81.647 kg

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

#### Contractual warranty

Warranty 18 months	
vvarrantv 18 months	