



#### Main

Device short name	C
Series name	Heavy duty

#### Complementary

[In] rated current	10 A
Body material	Zinc alloy
Contact code designation	Q600 A600
Contacts material	Silver alloy (Ag/Ni)
Contact operation	Snap action
Maximum displacement angle	90 °
Number of connectors	1 x orange 2 x red 3 x white 4 x black 1 x (ground connection) green
Specificity of operator	Low differential
Switch actuation	CW and CCW
Tilting angle	5 °
Torque value	0.5 N.m
Tripping angle	2 °
Connector type	5 pins mini connector


#### Environment

Ambient air temperature for operation	-20...185 °F
Product certifications	CSA[RETURN]CE[RETURN]UL listed

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.806 cm
Package 1 Width	10.16 cm
Package 1 Length	65.548 cm
Package 1 Weight	566.99 g

## Offer Sustainability

Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>