



Main

Range of product	9007
Series name	Heavy duty
Device short name	C
Head type	Turret head rotary lever
Material	Stainless steel
Type of operator	Spring return lever arm (to be ordered separately maintained)
Switch actuation	CW and CCW
Cable entry	NPT conduit entry, cable outer diameter: 12.70 mm
Contacts type and composition	1 NO/1 NC
Contact operation	Snap action

Complementary

Body material	Zinc alloy
Switch function	SPDT-DB
Contact form	Form Z
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	0.3 N.m
Tripping angle	45 °
Maximum displacement angle	90 °
[Ie] rated operational current	10 A, A600 10 A, Q600
[Ui] rated insulation voltage	600 V
Product certifications	UL listed[RETURN]CSA[RETURN]CE
Provided equipment	Receptacle


Environment

Ambient air temperature for operation	-29...85 °C
Environmental characteristic	Chemical pollution resistance

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.806 cm
Package 1 Width	10.16 cm
Package 1 Length	65.548 cm
Package 1 Weight	566.991 g

Offer Sustainability

Sustainable offer status	Green Premium product
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com