



Main

Device short name	C
Series name	Heavy duty

Complementary

[In] rated current	10 A
Body material	Zinc alloy
Contact code designation	A600 R300
Contacts material	Silver alloy (Ag/Ni)
Contact operation	Snap action
Electrical connection	9 x 2.44 m STOWA pre-wired cable
Maximum displacement angle	90 °
Number of connectors	1 x (ground connection) green 1 x white 2 x black 3 x red 4 x orange 5 x pink 6 x blue 7 x yellow 8 x brown
Specificity of operator	Low differential
Switch actuation	CW and CCW
Tilting angle	5 °
Torque value	0.5 N.m
Tripping angle	2 °

Environment


Ambient air temperature for operation	-20...185 °F
Product certifications	CSA[RETURN]UL listed[RETURN]CE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Environmental Disclosure	 Product Environmental Profile
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com