



Main

| | |
|-------------------|------------|
| Device short name | C |
| Series name | Heavy duty |

Complementary

| | |
|-------------------------------|--------------------------------|
| [In] rated current | 10 A |
| Body material | Zinc alloy |
| Contacts material | Silver alloy (Ag/Ni) |
| Contact operation | Snap action |
| Contacts type and composition | 2 NO/2 NC for switched neutral |
| Maximum displacement angle | 180 ° 90 ° |
| Specificity of operator | Standard pre-travel |
| Switch actuation | CW and CCW |
| Tilting angle | 10 ° |
| Torque value | 0.5 N.m |
| Tripping angle | 4 ° |

Environment

| | |
|---------------------------------------|--------------------------------|
| Ambient air temperature for operation | -20...185 °F |
| Product certifications | UL listed[RETURN]CE[RETURN]CSA |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 25.806 cm |
| Package 1 Width | 10.16 cm |
| Package 1 Length | 65.548 cm |
| Package 1 Weight | 566.99 g |

Offer Sustainability

| | |
|--|---|
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |