



Main

Range of product	9007
Series name	Heavy duty
Product or component type	Limit switch plug-in unit
Device short name	9007C
Body type	Standard plug-in
Product compatibility	9007C
Local display	Without
Number of poles	2
Contacts type and composition	2(NC-NO)
Contact operation	Snap action
Number of steps	2
Positive opening	Without
Ambient air temperature for operation	-29...85 °C for standard environment
Environmental characteristic	Standard environment
Sale per indivisible quantity	1

Complementary

Associated head	9007C
Associated connection component	9007CT62
Body material	Zinc
Function available	2 stages sequential
Switch function	2 SPDT-DB
Contact form	Form Z
Contacts material	Silver contacts
[Ie] rated operational current	1.2 A at 600 V AC, A600 conforming to NEMA rating designation 1.5 A at 480 V AC, A600 conforming to NEMA rating designation 3 A at 240 V AC, A600 conforming to NEMA rating designation 6 A at 120 V AC, A600 conforming to NEMA rating designation 0.11 A at 250 V DC, R300 conforming to NEMA rating designation 0.55 A at 125 V DC, R300 conforming to NEMA rating designation
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	600 V (pollution degree 3) conforming to UL 508 for contact block 600 V conforming to CSA C22.2 No 14
[Uimp] rated impulse withstand voltage	2.5 KV AC 1 min conforming to CE 2.2 kV AC 1 min conforming to UL
Short-circuit protection	10 A by CC fuse, protection type: non-time delay
Electrical durability	1000000 cycles
Mechanical durability	10000000 cycles
Terminals description ISO n°1	(7-8)NO (1-2)NC (3-4)NO (5-6)NC
Width	39.37 mm
Height	79.76 mm
Depth	45.47 mm
Net weight	0.57 kg


Environment

Shock resistance	60 gn for 9 ms conforming to IEC 60068-2-27
Vibration resistance	25 gn (f= 10...150 Hz) conforming to IEC 60068-2-6
NEMA degree of protection	NEMA 1 conforming to Nema type 250 NEMA 2 conforming to Nema type 250 NEMA 4 conforming to Nema type 250 NEMA 6 conforming to Nema type 250 NEMA 6P conforming to Nema type 250 NEMA 12 conforming to Nema type 250 NEMA 13 conforming to Nema type 250
IP degree of protection	IP67 conforming to IEC 60529
Electrical shock protection class	Class 0 conforming to IEC 61140
Ambient air temperature for storage	-20...185 °F
Protective treatment	Epoxy powder coat

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	25.806 cm
Package 1 Width	10.16 cm
Package 1 Length	65.548 cm
Package 1 Weight	566.991 g

Offer Sustainability

Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------