9007MS05G0302

Limit switch, 9007, ms cat whisker any direction spring rtn., 9' bottom cable



Main	
Range of product	9007
Series name	Miniature potted
Product or component type	Limit switch
Device short name	9007MS/ML
Sensor design	Miniature
Body type	Fixed
Head type	Multi-directional head
Material	Metal
Body material	Cast zinc
Number of poles	1

Complementary

Fixing mode	By the body
Movement of operating head	Multi-directional
Type of operator	Spring return wire whisker steel -
Type of approach	Multi-directional approach
Switch actuation	By any moving part
Contacts type and composition	NC-NO
Switch function	SPDT
Contact form	Form C
Contacts material	Gold flashed contacts
Contact operation	Snap action
Positive opening	Without
Electrical connection	Pre-wired cable bottom
Type of cable	SJTO cable (AWG 16), 2.74 m, yellow
Terminals description ISO n°1	(White)NO (Black)Com (Green-yellow)Gnd (red)NC
Wire insulation material	PVC
Maximum force for tripping	15 ozf
[le] rated operational current	100 MA at 125 V AC
	30 mA at 28 V DC
[Ithe] conventional enclosed thermal current	10 A
[Ithe] conventional enclosed thermal current [Ui] rated insulation voltage	
· ·	10 A 300 V (pollution degree 3) conforming to UL 508
[Ui] rated insulation voltage	10 A 300 V (pollution degree 3) conforming to UL 508 300 V (pollution degree 3) conforming to CSA C22.2 No 14
[Ui] rated insulation voltage Electrical durability	10 A 300 V (pollution degree 3) conforming to UL 508 300 V (pollution degree 3) conforming to CSA C22.2 No 14 100000 cycles
[Ui] rated insulation voltage Electrical durability Mechanical durability	10 A 300 V (pollution degree 3) conforming to UL 508 300 V (pollution degree 3) conforming to CSA C22.2 No 14 100000 cycles 10000000 cycles CSA UL
[Ui] rated insulation voltage Electrical durability Mechanical durability Marking	10 A 300 V (pollution degree 3) conforming to UL 508 300 V (pollution degree 3) conforming to CSA C22.2 No 14 100000 cycles 10000000 cycles CSA UL CE
[Ui] rated insulation voltage Electrical durability Mechanical durability Marking Sale per indivisible quantity	10 A 300 V (pollution degree 3) conforming to UL 508 300 V (pollution degree 3) conforming to CSA C22.2 No 14 100000 cycles 10000000 cycles CSA UL CE
[Ui] rated insulation voltage Electrical durability Mechanical durability Marking Sale per indivisible quantity Height	10 A 300 V (pollution degree 3) conforming to UL 508 300 V (pollution degree 3) conforming to CSA C22.2 No 14 100000 cycles 10000000 cycles CSA UL CE 1 44.45 mm

Environment

Shock resistance	35 gn for 9 ms conforming to IEC 60068-2-27	
Vibration resistance	10 gn (f= 751200 Hz) conforming to IEC 60529	
NEMA degree of protection	NEMA 1 conforming to Nema type 250 NEMA 12 conforming to Nema type 250 NEMA 13 conforming to Nema type 250	
IP degree of protection	IP54 conforming to IEC 60529	
Ambient air temperature for operation	-40220 °F	
Ambient air temperature for storage	-40220 °F	
Protective treatment	Epoxy powder coat	
Product certifications	UL[RETURN]CSA[RETURN]CE	
Standards	E78403 LR 25490 Class 32 11 03	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

Environmental Disclosure	Product Environmental Profile
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months