



### Main

Device application	Standard mill switch Standard foundry switch Heavy duty
Device short name	T
Series name	Severe duty

### Complementary

[Ith] conventional free air thermal current	20 A
[Ui] rated insulation voltage	600 V
Base plate style	Style D
Body material	Cast zinc
Contact code designation	P600 A600
Contact form	Form Z TPDT-SB
Contact status	Closed B for CCW position Open A for CCW position
Contacts material	Silver flashed copper
Contact operation	Snap action
Maximum displacement angle	88 °
Positive opening	Without
Switch actuation	CW and CCW
Tilting angle	14 °
Torque value	1.36 N.m
Tripping angle	12 °


### Environment

Ambient air temperature for operation	-10...185 °F
Electrical shock protection class	Class 0
IP degree of protection	IP67 IP66 IP65
NEMA degree of protection	NEMA 1/2/4/12/13
Product certifications	CE[RETURN]CSA[RETURN]UL listed
Protective treatment	Corrosion resistant gray paint
Shock resistance	30 gn
Standards	UL 508

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.89 cm
Package 1 Width	16.256 cm
Package 1 Length	7.366 cm
Package 1 Weight	1.134 kg

## Offer Sustainability

Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>