



Main

| | |
|--------------------|---|
| Device application | Standard mill switch Universal mill switch Heavy duty |
| Device short name | T |
| Series name | Severe duty |

Complementary

| | |
|---|-----------------------|
| [Ith] conventional free air thermal current | 20 A |
| [Ui] rated insulation voltage | 600 V |
| Base plate style | Style A |
| Body material | Cast zinc |
| Contact code designation | P600 A600 |
| Contacts material | Silver flashed copper |
| Contact operation | Snap action |
| Maximum displacement angle | 88 ° |
| Positive opening | Without |
| Switch actuation | CCW |
| Tilting angle | 14 ° |
| Torque value | 1.36 N.m |
| Tripping angle | 12 ° |


Environment

| | |
|---------------------------------------|--------------------------------|
| Ambient air temperature for operation | -10...185 °F |
| Electrical shock protection class | Class 0 |
| IP degree of protection | IP67 IP65 IP66 |
| NEMA degree of protection | NEMA 1/2/4/12/13 |
| Product certifications | UL listed[RETURN]CE[RETURN]CSA |
| Protective treatment | Corrosion resistant gray paint |
| Shock resistance | 30 gn |
| Standards | UL 508 |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 17.742 cm |
| Package 1 Width | 6.985 cm |
| Package 1 Length | 45.064 cm |
| Package 1 Weight | 1.134 kg |

Offer Sustainability

| | |
|--|---|
| Sustainable offer status | Green Premium product |
| Environmental Disclosure |  Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |