



Main

Series name	Severe duty
Device application	Universal mill switch Heavy duty Standard mill switch
Device short name	T
Head type	Rotary head

Complementary

Base plate style	Style C
Body material	Cast zinc
Switch actuation	CW
Electrical connection	Screw clamp terminal AWG 22...AWG 12
Cable entry	1 entry for Pg 13.5 conforming to DIN 40431
Switch function	SPDT-DB
Contact form	Form Z
Contact operation	Snap action
Contacts material	Silver flashed copper
Positive opening	Without
Minimum torque for tripping	1.4 N.m
Maximum actuation speed	90 Ft/Min with 45° cam angle, levers only 50 ft/min with 45° cam angle, levers only
Tripping angle	12 °
Maximum displacement angle	88 °
Repeat accuracy	+/- 0.004 in 0.1 mm
Contact code designation	A600 P600
[Ithe] conventional enclosed thermal current	20 A
[Ui] rated insulation voltage	600 V conforming to UL 508
[Uimp] rated impulse withstand voltage	2200 V AC conforming to UL 2500 V AC conforming to CE 2640 V AC conforming to CSA
Short-circuit protection	20 A Bussmann class CC KTK-R-20, type non-time delay
Contact status	Closed A for CCW position Open A for CW position Open B for CCW position Closed B for CW position Open B for initial position Closed A for initial position
Tilting angle	14 °
Type of operator	Spring return lever arm to be ordered separately Spring return


Environment

Shock resistance	30 gn
Vibration resistance	10 gn (f= 10...55 Hz)
NEMA degree of protection	NEMA 1/2/4/12/13
IP degree of protection	IP65 IP66 IP67
Electrical shock protection class	Class 0
Ambient air temperature for operation	-10...185 °F
Protective treatment	Corrosion resistant gray paint
Product certifications	CE[RETURN]UL listed[RETURN]CSA

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.89 cm
Package 1 Width	16.256 cm
Package 1 Length	7.366 cm
Package 1 Weight	1.134 kg

Offer Sustainability

Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com