

Main

Device short name	G
Enclosure type	Standard environment enclosure for indoor
Factory modification	3-way lever (ON-AUTO-OFF)
Product specific application	Control electrically driven water pumps and air compressors
Range of product	Square D Pumptrol
Switch application	Standard

Complementary

Approximate adjustable differential	27.58...55.16 kPa
Depth	93.47 mm
Electrical connection	screw clamp terminal
Fixing mode	By brackets
Fluid connection type	0.25 inch NPSF internal
Height	145.29 mm
Material	Zinc plated steel: flange
Materials in contact with fluid	Nitrile (Buna-N) diaphragm
Maximum pressure	100 psig
Motor power hp	2 Hp at 230 V AC, 1 phase 1 Hp at 115 V AC, 1 phase 2 hp at 460/575 V AC, 1 phase
Number of poles	2
Permissible voltage	575 V AC
Pressure actuator	Diaphragm
Net weight	1.02 kg
Range on decreasing pressure	68.95...241.32 KPa 37.92...210.29 kPa
Scale type	Adjustable differential
Switch function	DPDT
Width	87.38 mm

Environment

NEMA degree of protection	NEMA 1
Product certifications	UL listed file E12158 CCN NKPZ[RETURN]CSA file LR25490

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

California proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Diisodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

For all Reach Rohs enquiries contact us at

sustainability@tesensors.com