



Main

Device short name	C
Enclosure type	Dust and damp proof weatherproof enclosure for indoor/outdoor
Product specific application	Condensation pump
Switch application	Standard

Complementary

Electrical connection	Screw clamp terminal
Float movement	6.5...13 in
Float position	Left
Material	Stainless steel: float/rod Nitrile (Buna-N): seal ring
Motor power hp	3 Hp at 115 V AC, 3 phases 2 Hp at 115 V AC, 1 phase 1 Hp at 460/575 V AC, 3 phases 5 Hp at 230 V AC, 1 phase 3 hp at 230 V AC, 3 phases
Mounting support	Flange
Number of poles	2
Permissible voltage	575 V AC
Switch function	DPST

Environment

NEMA degree of protection	NEMA 4
---------------------------	--------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	29.871 cm
Package 1 Width	11.76 cm
Package 1 Length	75.872 cm
Package 1 Weight	9.73 kg

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com