SC656ABV0

Hyde Park, Ultrasonic sensor, analog, voltage (V), 18 mm barrel, 15 24 V DC



Main

Series name Superprox + Device short name SC656 Sensor design Cylindrical M18 Type of sensing window Material Plastic Enclosure material ULTEM Front material Silicone rubber Type of output signal Analog ISO thread M18 x 1 Wiring technique [Us] rated supply voltage limits Supply voltage limits 1328 V DC Analogue output range Electrical connection Male connector M12 4 pins Product specific application	Range of product	Hyde Park
Device short name SC656 Sensor design Cylindrical M18 Type of sensing window Configurable Material Plastic Enclosure material ULTEM Front material Silicone rubber Type of output signal Analog ISO thread M18 x 1 Wiring technique 4-wire [Us] rated supply 1524 V DC with overload and short-circuit voltage protection Supply voltage limits 1328 V DC Analogue output range 010 V configurable Electrical connection Male connector M12 4 pins Product specific Analog output	Sensor type	Ultrasonic sensor
Sensor design Cylindrical M18 Type of sensing window Configurable Material Plastic Enclosure material ULTEM Front material Silicone rubber Type of output signal Analog ISO thread M18 x 1 Wiring technique 4-wire [Us] rated supply 1524 V DC with overload and short-circuit voltage protection Supply voltage limits 1328 V DC Analogue output range 010 V configurable Electrical connection Male connector M12 4 pins Product specific Analog output	Series name	Superprox +
Type of sensing window Material Plastic Enclosure material ULTEM Front material Silicone rubber Type of output signal ISO thread M18 x 1 Wiring technique [Us] rated supply voltage Supply voltage limits 1328 V DC Analogue output range Electrical connection Male connector M12 4 pins Product specific Analog output	Device short name	SC656
Material Plastic Enclosure material ULTEM Front material Silicone rubber Type of output signal Analog ISO thread M18 x 1 Wiring technique 4-wire [Us] rated supply 1524 V DC with overload and short-circuit voltage protection Supply voltage limits 1328 V DC Analogue output range 010 V configurable Electrical connection Male connector M12 4 pins Product specific Analog output	Sensor design	Cylindrical M18
Enclosure material Front material Silicone rubber Type of output signal ISO thread M18 x 1 Wiring technique 4-wire [Us] rated supply voltage protection Supply voltage limits 1328 V DC Analogue output range Electrical connection Male connector M12 4 pins Product specific ULTEM Silicone rubber 4-wire 1524 V DC with overload and short-circuit protection Supply voltage limits 1328 V DC Analogue output range Analog output	Type of sensing window	Configurable
Front material Silicone rubber Type of output signal ISO thread M18 x 1 Wiring technique [Us] rated supply voltage protection Supply voltage limits 1328 V DC Analogue output range 010 V configurable Electrical connection Male connector M12 4 pins Product specific Analog output	Material	Plastic
Type of output signal Analog ISO thread M18 x 1 Wiring technique 4-wire [Us] rated supply 1524 V DC with overload and short-circuit voltage protection Supply voltage limits 1328 V DC Analogue output range 010 V configurable Electrical connection Male connector M12 4 pins Product specific Analog output	Enclosure material	ULTEM
ISO thread M18 x 1 Wiring technique 4-wire [Us] rated supply voltage	Front material	Silicone rubber
Wiring technique [Us] rated supply 1524 V DC with overload and short-circuit voltage protection Supply voltage limits 1328 V DC Analogue output range 010 V configurable Electrical connection Male connector M12 4 pins Product specific Analog output	Type of output signal	Analog
[Us] rated supply voltage protection Supply voltage limits 1328 V DC Analogue output range 010 V configurable Electrical connection Male connector M12 4 pins Product specific Analog output	ISO thread	M18 x 1
voltage protection Supply voltage limits 1328 V DC Analogue output range 010 V configurable Electrical connection Male connector M12 4 pins Product specific Analog output	Wiring technique	4-wire
Analogue output range 010 V configurable Electrical connection Male connector M12 4 pins Product specific Analog output		
Electrical connection Male connector M12 4 pins Product specific Analog output	Supply voltage limits	1328 V DC
Product specific Analog output	Analogue output range	010 V configurable
	Electrical connection	Male connector M12 4 pins
	•	Analog output

Complementary

[Sn] nominal sensing distance	254 mm
Blind zone	19 mm
Transmission frequency	500 kHz
Beam angle	10 °
Minimum size of detected object	Cylinder diameter 1.59 mm - up to 76.2 mm sensing distance
Current consumption	50 mA
Maximum switching current	100 mA with reverse polarity protection
Height	18 mm
Width	18 mm
Depth	18 mm
Length	73.91 mm
Net weight	0.033 kg

Environment

Product certifications	UL	
Marking	CE	
NEMA degree of protection	NEMA 4X (indoor use only)	
IP degree of protection	IP67	
Ambient air temperature for operation	060 °C	
Ambient air temperature for storage	-40100 °C	
Relative humidity	100 % without condensation	
Vibration resistance	+/-1 mm conforming to IEC 60068-2-6 (f = 1055 Hz)	
Shock resistance	30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27	
Resistance to electromagnetic fields	10 V/m level 3 conforming to IEC 61000-4-3	
Resistance to fast transients	1 kV level 3 conforming to IEC 61000-4-4	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.415 cm	
Package 1 Width	3.81 cm	
Package 1 Length	8.415 cm	
Package 1 Weight	13.608 g	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months

