SGA8176

Coded magnetic system, MAGNET SWITCH, 10 VA, 250 V dc / 135 V ac, 0.5 A max



Coded magnetic system	
1 NO	
Plastic	
Pre-cabled	
250 V DC	
	1 NO Plastic Pre-cabled

Complementary

Protection type	Overload and short-circuit protection
Breaking capacity	10 VA

Environment

Ambient air temperature for operation	-2570 °C	2
Ambient air temperature for storage	-4085 °C	4

Packing Units

201111-19 0 1 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	18.542 cm	
Package 1 Width	5.08 cm	
Package 1 Length	18.542 cm	
Package 1 Weight	213.188 g	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intermed as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the documentation in the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.