SGA8182L05

Coded magnetic system, MAGNET SWITCH, 10 VA max, 200 V dc / 500 mA max cable I = 5 m



Main	
Product or component type	Coded magnetic system
Contacts type and composition	1 NO
Material	Plastic
Electrical connection	Pre-cabled
Cable length	5 m
[Ue] rated operational voltage	200 V DC

Complementary

Protection type	Overload and short-circuit protection
Breaking capacity	10 VA

Environment

Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4085 °C	

Packing Units

1 doking office		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	14.288 cm	
Package 1 Width	14.288 cm	
Package 1 Length	14.288 cm	
Package 1 Weight	127.006 g	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not interest of and is not to be used for determining suitability or flushed products for specific user applications. It is the documentation is not integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.