# SM850A1200

# Hyde Park, microsonic thru beam transmitter



#### Main

Range of product	Hyde Park
Sensor type	Ultrasonic sensor
Series name	Standard format
Device short name	SM850
Sensor design	Cylindrical Ø 12 mm plain
Material	Stainless steel
[Us] rated supply voltage	1224 V DC
Electrical connection	1 connector micro
[Sd] sensing range	0.305 m
IP degree of protection	IP67

## Complementary

[Sn] nominal sensing distance	0.305 m
Type of sensing window	Fixed
Condition of use	Thru beam

#### **Environment**

Product certifications CE	
---------------------------	--

## **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.415 cm	
Package 1 Width	3.81 cm	
Package 1 Length	8.415 cm	
Package 1 Weight	362.874 g	

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com