SM950A100000

Hyde Park, ultrasonic sensor cylindrical M30, Sn1m, NO, 12...24 VDC, M12



Main

Range of product	Hyde Park
Sensor type	Ultrasonic sensor
Series name	Superprox 900
Device short name	SM950
Sensor design	Cylindrical M30
Type of sensing window	Adjustable
Material	Plastic
Enclosure material	ULTEM
Front material	Silicone rubber
Type of output signal	Discrete
Discrete output function	1 NO
ISO thread	M30 x 1.5
Wiring technique	4-wire
[Us] rated supply voltage	1224 V DC with overload and short-circuit protection
Supply voltage limits	1028 V DC
Discrete output type	PNP/NPN
Electrical connection	Male connector M12 4 pins
Product specific application	-

Complementary

Complementary	
[Sn] nominal sensing distance	1 m
[Sd] sensing range	0.05081 m
[Sa] assured operating distance	0.05081 m teach push-button
Maximum differential travel	2.5 mm
Blind zone	051 mm
Transmission frequency	200 kHz
Repeat accuracy	0.87 %
Minimum size of detected object	Cylinder diameter 1.6 mm - up to 305 mm sensing distance
Current consumption	100 mA
Maximum switching current	100 mA with reverse polarity protection
Resistance to electrostatic discharge	8 kV level 4 conforming to IEC 61000-4-2
Height	30 mm
Width	34.7 mm
Depth	30 mm
Length	96 mm
Net weight	0.26 kg

Environment

Product certifications	UL
Marking	CE
NEMA degree of protection	NEMA 4X (indoor use only)
IP degree of protection	IP67
Ambient air temperature for operation	050 °C
Ambient air temperature for storage	-2080 °C
Relative humidity	100 % without condensation

1

Vibration resistance	+/-1 mm conforming to IEC 60068-2-6 (f = 1055 Hz)
Shock resistance	30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27
Resistance to electromagnetic fields	10 V/m level 3 conforming to IEC 61000-4-3
Resistance to fast transients	1 kV level 3 conforming to IEC 61000-4-4

Packing Units

PCE
1
4.572 cm
9.906 cm
13.462 cm
117.934 g

Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------