# VM18PPO0000Q

Hyde Park, ultrasonic sensor cylindrical M18, dual level Sn508mm, NO, 12...24 VDC, M12



#### Main

Range of product	Hyde Park
Sensor type	Ultrasonic sensor
Series name	Virtu VM18
Device short name	VM18
Sensor design	Cylindrical M18
Type of sensing window	Adjustable
Material	Plastic
Enclosure material	PBT
Front material	Glass epoxy
Type of output signal	Discrete
Discrete output function	1 NO
ISO thread	M18 x 1
Wiring technique	4-wire
[Us] rated supply voltage	1224 V DC with overload and short-circuit protection
Supply voltage limits	1028 V DC
Discrete output type	PNP
Electrical connection	Male connector M12 4 pins
Product specific application	Dual-level - pump-out latch
·	

#### Complementary

508 mm	
50.8508 mm	
50.8508 mm remote teach push-button	
051 mm	
300 kHz	
1.27 %	
5 °	
Cylinder diameter 2.5 mm - up to 200 mm sensing distance	
Output not active: 1 LED (green)	
40 mA	
100 mA with reverse polarity protection	
8 kV level 4 conforming to IEC 61000-4-2	
18 mm	
18 mm	
18 mm	
77.62 mm	
0.033 kg	
	50.8508 mm remote teach push-button  051 mm  300 kHz  1.27 %  5 °  Cylinder diameter 2.5 mm - up to 200 mm sensing distance  Output not active: 1 LED (green)  40 mA  100 mA with reverse polarity protection  8 kV level 4 conforming to IEC 61000-4-2  18 mm  18 mm  18 mm  77.62 mm

#### **Environment**

Standards	IEC 60947
Product certifications	UL
Marking	CE
NEMA degree of protection	NEMA 4X (indoor use only)
IP degree of protection	IP67
Ambient air temperature for operation	-3070 °C

Ambient air temperature for storage	-4085 °C
Relative humidity	100 % without condensation
Vibration resistance	+/-1 mm conforming to IEC 60068-2-6 (f = 1055 Hz)
Shock resistance	30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27
Resistance to electromagnetic fields	10 V/m level 3 conforming to IEC 61000-4-3
Resistance to fast transients	1 kV level 3 conforming to IEC 61000-4-4

### Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.415 cm	
Package 1 Width	1.27 cm	
Package 1 Length	8.415 cm	
Package 1 Weight	90.719 g	

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

### Contractual warranty

Warranty	18 months	