## XCCRAS06U25

shaft coupling - for encoder - homokinetic with bellows Ø 6 mm to 0.25 inch



Main	
Product or component type	Shaft coupling
Accessory / separate part destination	Rotary encoder with solid shaft
Accessory / separate part categor	Coupling accessories
Accessory / separate part type	Homokinetic with bellow
Bore diameter encoder side	6 mm
Bore diameter machine side	6.35 mm

## Complementary

Collar material	Aluminium
Bellow material	Stainless steel
Maximum angular misalignment	4°
Maximum axial misalignment	+/- 0.5 mm
Maximum lateral misalignment	+/- 0.3 mm
Maximum torque value	0.8 N.m
Net weight	0.018 kg

#### **Packing Units**

. coming or me		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2 cm	
Package 1 Width	2 cm	
Package 1 Length	3.5 cm	
Package 1 Weight	20 g	


#### Offer Sustainability

<u> </u>	
Toxic heavy metal free	Yes
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

# Product data sheet Dimensions Drawings

# XCCRAS06U25

## **Dimensions**



Ø e	Øs
6 mm	6.35 mm