### XCCRAS1212

shaft coupling - for encoder - homokinetic with bellows  $\emptyset$  12 to 12 mm



Main		
Product or component type	Shaft coupling	
Accessory / separate part destination	Rotary encoder with solid shaft	
Accessory / separate part categor	Coupling accessories	
Accessory / separate part type	Homokinetic with bellow	
Bore diameter encoder side	12 mm	
Bore diameter machine side	12 mm	

#### Complementary

Bellow material  Maximum angular misalignment  4°  Maximum axial misalignment  +/- 0.5 mm  Maximum lateral misalignment  +/- 0.3 mm  Maximum torque value  0.8 N.m	
Maximum axial misalignment +/- 0.5 mm  Maximum lateral misalignment +/- 0.3 mm	
Maximum lateral misalignment +/- 0.3 mm	
<del>_</del>	
Maximum torque value 0.8 N.m	
Net weight 0.01 kg	

#### **Packing Units**

3 - 3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	10 cm	
Package 1 Width	15 cm	
Package 1 Length	12.5 cm	
Package 1 Weight	500 g	

#### Offer Sustainability

Toxic heavy metal free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com


#### Contractual warranty

Contractadi Warranty		
Warranty	18 months	

# Product data sheet Dimensions Drawings

## XCCRAS1212

#### **Dimensions**



Ø e	Øs
12 mm	12 mm