

XCCRAS12U37

shaft coupling - for encoder - homokinetic with bellows Ø 12 mm to 0.375 inch



Main

Product or component type	Shaft coupling
Accessory / separate part destination	Rotary encoder with solid shaft
Accessory / separate part category	Coupling accessories
Accessory / separate part type	Homokinetic with bellow
Bore diameter encoder side	12 mm
Bore diameter machine side	9.525 mm

Complementary


Collar material	Aluminium
Bellow material	Stainless steel
Maximum angular misalignment	4°
Maximum axial misalignment	+/- 0.5 mm
Maximum lateral misalignment	+/- 0.3 mm
Maximum torque value	0.8 N.m
Net weight	0.013 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Dimensions



$\varnothing e$	$\varnothing s$
12 mm	9.53 mm