


# XCKD2101M12

Limit switch, Limit switches XC Standard, XCKD, with rotary head w/o operating lever, 1NC+1 NO, snap, M12



## Main

|                               |  |
|-------------------------------|--|
| Range of product              | Telemecanique Limit switches XC Standard |
| Series name                   | Standard format                          |
| Product or component type     | Limit switch                             |
| Device short name             | XCKD                                     |
| Sensor design                 | Compact                                  |
| Body type                     | Fixed                                    |
| Head type                     | Rotary head                              |
| Material                      | Metal                                    |
| Body material                 | Zamak                                    |
| Head material                 | Zamak                                    |
| Fixing mode                   | By the body                              |
| Movement of operating head    | Rotary                                   |
| Type of operator              | Spring return without operating lever    |
| Type of approach              | Lateral approach, 2 directions           |
| Number of poles               | 2  |
| Contacts type and composition | 1 NC + 1 NO                              |
| Contact operation             | Snap action                              |

## Complementary

|  |   |
|--|---|
| Electrical connection                        | Male connector M12, 5 pins  |
| Contacts insulation form                     | Zb  |
| Positive opening                             | With  |
| Positive opening minimum torque              | 0.25 N.m  |
| Minimum torque for tripping                  | 0.1 N.m   |
| Maximum actuation speed                      | 1.5 m/s   |
| [Ie] rated operational current               | 3 A at 50 V, AC-15 conforming to EN/IEC 60947-5-1 appendix A<br>0.27 A at 50 V, DC-13 conforming to EN/IEC 60947-5-1 appendix A   |
| [Ithe] conventional enclosed thermal current | 4 A   |
| [Ui] rated insulation voltage                | 60 V (pollution degree 3) conforming to IEC 60947-1   |
| Maximum resistance across terminals          | 25 MOhm conforming to IEC 60255-7 category 3  |
| [Uimp] rated impulse withstand voltage       | 0.8 kV conforming to IEC 60664<br>0.8 kV conforming to IEC 60947-1  |
| Short-circuit protection                     | 4 A cartridge fuse, type gG   |
| Electrical durability                        | 5000000 Cycles, DC-13, 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Mechanical durability                        | 10000000 cycles   |
| Width  | 31 mm   |
| Height                                       | 65 mm   |
| Depth  | 30 mm   |
| Net weight                                   | 0.195 kg  |
| Terminals description ISO n°1                | (21-22)NC<br>(13-14)NO  |

## Environment

|                                       |   |
|---------------------------------------|---|
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27  |
| Vibration resistance                  | 25 gn (f= 10...500 Hz) conforming to IEC 60068-2-6                                      |
| IK degree of protection               | IK06 conforming to EN 50102   |
| Electrical shock protection class     | Class I conforming to IEC 61140<br>Class I conforming to NF C 20-030                    |
| Ambient air temperature for operation | -25...70 °C   |
| Ambient air temperature for storage   | -40...70 °C   |
| Protective treatment                  | TC  |
| Product certifications                | CSA[RETURN]CCC[RETURN]UL  |
| Standards                             | CSA C22.2 No 14<br>IEC 60204-1<br>UL 508<br>IEC 60947-5-1<br>EN 60947-5-1<br>EN 60204-1 |

## Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 3.3 cm |
| Package 1 Width              | 3.9 cm |
| Package 1 Length             | 10 cm  |
| Package 1 Weight             | 200 g  |


## Offer Sustainability

|  |   |
|--|---|
| Sustainable offer status                   | Green Premium product   |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|


## Dimensions



- (1) Tapped entry for M12
- (2) 2 elongated holes Ø 4.3 x 6.3 mm on 22 mm centres, 2 holes Ø 4.3 on 20 mm centres.
- (3) 2 x Ø 3 holes for support studs, depth 4 mm.

## Mounting with Cable Entry


### Position of Cable Gland



- (1) Recommended
- (2) To be avoided


## Mounting with Rotary Heads and Levers

### Type of Cam



- (1) Recommended
- (2) To be avoided

## Setting-up with Head ZCE01 and ZCE09



- (1) Tightening torque (Min : 1) (Max : 1.5)
- (2) Tightening torque (Min : 0.8) (Max : 1.2)

---

## Wiring Diagram

---

2-pole NC + NO Snap Action




---

## Connections

---


### M12 Connector




1-2 : NC  
3-4 : NO  
5 : Grounding

Characteristics of Actuation

Switch Actuation on End



Functionnal Diagram



- (1) Closed
- (2) Open
- (4) Tripping
- (5) Resetting

- (1) Closed
- (2) Open
- (4) Tripping
- (5) Resetting