



Main	
Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Device short name	XCKM
Material	Metal
Body material	Zamak
Fixing mode	By the body
Movement of operating head	Linear Rotary
Number of poles	2
Contacts type and composition	1 NC + 1 NO

Complementary

Switch actuation	By 30° cam
Contacts insulation form	Zb
Number of steps	1
Positive opening	With
Positive opening minimum torque	0.25 N.m
Minimum force for tripping	8 N
Maximum actuation speed	1.5 m/s
Width	64 mm
Height	64 mm
Depth	30 mm

Environment

Ambient air temperature for operation	-25...70 °C
Standards	-

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.