

# XCKS541H29

Limit switch, Limit switches XC Standard, XCKS, thermoplastic plastic roller lever var. length, 1NC+1 NO, slow, M20



## Main

|                               |                                                                           |
|-------------------------------|---------------------------------------------------------------------------|
| Range of product              | Telemecanique Limit switches XC Standard                                  |
| Series name                   | Standard format                                                           |
| Product or component type     | Limit switch                                                              |
| Device short name             | XCKS                                                                      |
| Sensor design                 | -                                                                         |
| Body type                     | Fixed                                                                     |
| Head type                     | Rotary head                                                               |
| Material                      | Plastic                                                                   |
| Body material                 | Plastic                                                                   |
| Head material                 | Plastic                                                                   |
| Fixing mode                   | By the body                                                               |
| Movement of operating head    | Rotary                                                                    |
| Type of operator              | Spring return roller lever thermoplastic variable length                  |
| Type of approach              | Lateral approach, 1 or 2 programmable direction                           |
| Cable entry                   | 1 entry tapped for M20 x 1.5 cable gland, cable outer diameter: 7...13 mm |
| Number of poles               | 2                                                                         |
| Contacts type and composition | 1 NC + 1 NO                                                               |
| Contact operation             | Slow-break, break before make                                             |

## Complementary

|                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Switch actuation                             | By 30° cam                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Electrical connection                        | Screw-clamp terminals, clamping capacity: 1 x 0.5...2 x 2.5 mm <sup>2</sup>                                                                                                                                                                                                                                                                                                                                                           |
| Contacts insulation form                     | Zb                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Number of steps                              | 1                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Positive opening                             | With                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Minimum torque for tripping                  | 0.1 N.m                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Minimum actuation speed                      | 6 m/min                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Maximum actuation speed                      | 1.5 m/s                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Contact code designation                     | A300, AC-15 (Ue = 240 V), Ie = 3 A conforming to EN/IEC 60947-5-1 appendix A<br>Q300, DC-13 (Ue = 250 V), Ie = 0.27 A conforming to EN/IEC 60947-5-1 appendix A                                                                                                                                                                                                                                                                       |
| [Ithe] conventional enclosed thermal current | 10 A AC                                                                                                                                                                                                                                                                                                                                                                                                                               |
| [Ui] rated insulation voltage                | 300 V conforming to UL 508<br>500 V (pollution degree 3) conforming to IEC 60947-1<br>300 V conforming to CSA C22.2 No 14                                                                                                                                                                                                                                                                                                             |
| Maximum resistance across terminals          | 25 MOhm conforming to IEC 60255-7 category 3                                                                                                                                                                                                                                                                                                                                                                                          |
| [Uimp] rated impulse withstand voltage       | 6 kV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1                                                                                                                                                                                                                                                                                                                                                                        |
| Short-circuit protection                     | 10 A cartridge fuse, type gG                                                                                                                                                                                                                                                                                                                                                                                                          |
| Electrical durability                        | 5000000 Cycles, DC-13, inductive load type, 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 Cycles, DC-13, inductive load type, 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, inductive load type, 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |

|                               |                        |
|-------------------------------|------------------------|
| Mechanical durability         | 20000000 cycles        |
| Width                         | 40 mm                  |
| Height                        | 117...172 mm           |
| Depth                         | 57 mm                  |
| Net weight                    | 0.165 kg               |
| Terminals description ISO n°1 | (21-22)NC<br>(13-14)NO |

## Environment

|                                       |                                                                                                             |
|---------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27                                                                |
| Vibration resistance                  | 25 gn (f= 10...500 Hz) conforming to IEC 60068-2-6                                                          |
| IP degree of protection               | IP67 conforming to IEC 60529<br>IP66 conforming to IEC 60529                                                |
| IK degree of protection               | IK05 conforming to EN 50102                                                                                 |
| Electrical shock protection class     | Class II conforming to IEC 61140<br>Class II conforming to NF C 20-030                                      |
| Overvoltage category                  | Class II conforming to IEC 61140<br>Class II conforming to NF C 20-030                                      |
| Ambient air temperature for operation | -25...70 °C                                                                                                 |
| Ambient air temperature for storage   | -40...70 °C                                                                                                 |
| Protective treatment                  | TC                                                                                                          |
| Product certifications                | CSA[RETURN]CCC[RETURN]UL                                                                                    |
| Standards                             | UL 508<br>IEC 60947-5-1<br>EN 60947-5-1<br>CSA C22.2 No 14<br>EN 60204-1<br>CENELEC EN 50041<br>IEC 60204-1 |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 4.200 cm  |
| Package 1 Width              | 9.700 cm  |
| Package 1 Length             | 13.500 cm |
| Package 1 Weight             | 187.000 g |
| Unit Type of Package 2       | S02       |
| Number of Units in Package 2 | 22        |
| Package 2 Height             | 15.000 cm |
| Package 2 Width              | 30.000 cm |
| Package 2 Length             | 40.000 cm |
| Package 2 Weight             | 4.535 kg  |

## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

- (1) 1 tapped entry for M20 x 1.5
- (2) 2 elongated holes  $\varnothing 5.3 \times 7.3$ .

## Mounting with Cable Entry

### Position of Cable Gland



- (1) Recommended
- (2) To be avoided

## Mounting with Rotary Heads and Levers

### Type of Cam



- (1) Recommended
- (2) To be avoided

## Setting-up

### Head Rotation Adjustment



C : 1 Nm (+/- 20%) / 8.85 lb-in (+/- 20%)

## Setting-up

## Lever Angle Adjustment



C : 1 Nm (+/- 20%) / 8.85 lb-in (+/- 20%)

## Setting-up with Head ZCKD05

### Direction of Actuation Programming




C : 1 Nm (+/- 20%) / 8.85 lb-in (+/- 20%)

---

## Wiring Diagram

---

2-pole NC + NO Break Before Make, Slow Break



---

## Characteristics of Actuation

---

### Switch Actuation by 30° Cam



---

## Functionnal Diagram

---

