

# XCMD2515AM4

Limit switch, Limit switches XC Standard,  
XCMD, plastic lever, 1NC+1 NO, slow, AMP 4P



## Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch
Device short name	XCMD
Sensor design	Miniature
Body type	Plug-in body
Head type	Rotary head
Material	Metal
Body material	Zamak
Head material	Zamak
Fixing mode	By the body
Movement of operating head	Rotary
Type of operator	Spring return roller lever thermoplastic
Type of approach	Lateral approach, 2 directions
Number of poles	2
Contacts type and composition	1 NC + 1 NO
Contact operation	Slow-break

## Complementary

Tracks	24/31 mm
Switch actuation	By 30° cam
Electrical connection	Male connector AMP connector, 4 pins
Contacts insulation form	Zb
Positive opening	With
Positive opening minimum force	0.5 N
Minimum force for tripping	0.1 N
Maximum actuation speed	1.5 m/s
[Ie] rated operational current	1 A at 24 V, DC-13 conforming to EN/IEC 60947-5-1 appendix A 3 A at 24 V, AC-14
[Ithe] conventional enclosed thermal current	6 A
[Ui] rated insulation voltage	36 V (pollution degree 3) conforming to IEC 60947-5-1
Maximum resistance across terminals	25 mOhm conforming to IEC 60255-7 category 3
[Uimp] rated impulse withstand voltage	0.8 kV conforming to IEC 60664 0.8 kV conforming to IEC 60947-1
Short-circuit protection	6 A cartridge fuse, type gG
Electrical durability	5000000 cycles, DC-13, 24 V, 3 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C
Mechanical durability	10000000 cycles
Width	32 mm
Height	112 mm
Depth	33 mm
Net weight	0.13 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

Shock resistance	25 gn for 18 ms conforming to IEC 60068-2-27
Vibration resistance	5 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
IP degree of protection	IP66 conforming to IEC 60529 IP67 conforming to IEC 60529 IP69 conforming to IEC 60529
IK degree of protection	IK06 conforming to EN 62262
Electrical shock protection class	Class III conforming to IEC 61140 Class III conforming to NF C 20-030
Ambient air temperature for operation	-25...70 °C
Ambient air temperature for storage	-40...70 °C
Protective treatment	TC
Product certifications	cURus[RETURN]CCC
Standards	UL 508 CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60204-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	3.3 cm
Package 1 Length	11.5 cm
Package 1 Weight	110.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	50
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	6.152 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>

## Contractual warranty

Warranty	18 months
----------	-----------

Technical drawing of the 1000 Series Hydraulic Cylinder, showing side and front views with dimensions in mm and inches.

**Side View Dimensions:**

- Top flange width: 31 mm (1.22 in.)
- Top flange thickness: 24 mm (0.94 in.)
- Top flange hole diameter: 5.5 mm (0.21 in.)
- Body diameter: 16 mm (0.62 in.)
- Body length: 17.6 mm (0.69 in.)
- Base diameter: 32.4 mm (1.27 in.)

**Front View Dimensions:**

- Top flange hole diameter: Ø 16 mm (Ø 0.62 in.)
- Top flange thickness: 34.4 mm (1.35 in.)
- Top flange hole offset: 1.35 mm (0.05 in.)
- Top flange hole diameter: 54 mm (2.12 in.)
- Body diameter: 58.1 mm (2.28 in.)
- Body length: 112.1 mm (4.41 in.)
- Base diameter: 20 mm (0.78 in.)
- Base length: 31.9 mm (1.25 in.)


**Detail View:**

- Top flange hole offset: 15°
- Top flange hole offset: 15°




## Mounting with Roller Lever

### Recommended Mounting



### Mounting to be Avoided




---

## Connections and Schema

---

### Wiring Diagram

2-pole NC + NO break before make, slow break




---

## Connections and Schema

---

### AMP Superseal 1.5 Male Connector



1 : NC

2 : NC


3 : NO

4 : NO

## Technical Description


### Characteristics of Actuation

Switch Actuation by 30° cam



## Technical Description

### Functional Diagram, Travel Distance



(P) : Positive opening point

(1) : NC contact with positive opening operation

(2) : Closed

(3) : Open

BK : Black

BK-WH : Black White

BU : Blue

BN : Brown