

### Main

Device short name	XCSE
Enclosure type	Dust and damp proof enclosure for indoor/outdoor Corrosion resistance enclosure for indoor/outdoor

### Complementary

[In] rated current	6 A
[Us] rated supply voltage	24 V
Actuator	Key
Cable entry	Conduit entry electromagnet connection
Contact operation	Slow-break, break before make
Contacts type and composition	1 NO for staggered 2 NC
Depth	43.94 mm
Enclosure material	metal enclosure
Height	146.05 mm
Installation direction	Actuator supply: 90°
Locking options description	With locking of actuator, unlocking by key operated lock With interlocking, locking by solenoid
Number of poles	3
Permissible voltage	300 V AC
Pilot light	LED orange LED green

### Environment

Ambient air temperature for operation	-25...40 °C
IP degree of protection	IP67
NEMA degree of protection	NEMA 4/4X/12

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	16.0 cm
Package 1 Length	23.0 cm
Package 1 Weight	1.361 kg

## Offer Sustainability

---

California proposition 65

WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

---

For all Reach Rohs enquiries contact us at

[sustainability@tesensors.com](mailto:sustainability@tesensors.com)

---