



### Main

|                   |  |
|-------------------|--|
| Device short name | XCSL   |
| Enclosure type    | Water resistant enclosure for indoor/outdoor<br>Dustproof enclosure for indoor/outdoor<br>Ice/sleet proof enclosure for indoor/outdoor |

### Complementary

|                               |  |
|-------------------------------|--|
| [In] rated current            | 10 A   |
| [Us] rated supply voltage     | 110 V AC   |
| Actuator                      | Key  |
| Contact operation             | Slow-break, break before make                            |
| Contacts type and composition | 1 NO for staggered<br>2 NC                               |
| Depth                         | 43.94 mm   |
| Enclosure material            | metal enclosure  |
| Height                        | 194.06 mm  |
| Installation direction        | Electromagnet connection: left<br>Actuator supply: right |
| Key locking position          | Front  |
| Locking options description   | With locking of actuator, unlocking by key operated lock |
| Number of poles               | 3  |
| Permissible voltage           | 300 V AC   |
| Pilot light                   | LED orange   |

### Environment

|                                       |                 |
|---------------------------------------|-----------------|
| Ambient air temperature for operation | -13...158 °F    |
| IP degree of protection               | IP67            |
| NEMA degree of protection             | NEMA 1/2/3/4/12 |

### Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 5.2 cm    |
| Package 1 Width              | 6.2 cm    |
| Package 1 Length             | 28.0 cm   |
| Package 1 Weight             | 980.0 g   |
| Unit Type of Package 2       | S02       |
| Number of Units in Package 2 | 10        |
| Package 2 Height             | 15.0 cm   |
| Package 2 Width              | 30.0 cm   |
| Package 2 Length             | 40.0 cm   |
| Package 2 Weight             | 10.255 kg |

## Offer Sustainability

|  |   |
|--|---|
| Sustainable offer status                   | Green Premium product   |
| Circularity Profile                        | No need of specific recycling operations  |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>  |