

# XCSLE2727512

Safety switch, Telemecanique Safety switches XCS, plastic XCSLE, 4 NC, slow break, 3 entries tapped M20, 24 V



## Main

|                                                          |                                                                                                                                                                                          |
|----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product                                         | Telemecanique Safety switches XCS                                                                                                                                                        |
| Product or component type                                | Safety switch                                                                                                                                                                            |
| Component name                                           | XCSLE                                                                                                                                                                                    |
| Design                                                   | Slim                                                                                                                                                                                     |
| Material                                                 | Plastic                                                                                                                                                                                  |
| Head type                                                | Key operated turret head                                                                                                                                                                 |
| Contacts type and composition                            | 2 NC                                                                                                                                                                                     |
| Contact operation                                        | Slow-break, simultaneous                                                                                                                                                                 |
| Solenoid contacts type and composition                   | 2 NC (slow-break, simultaneous)                                                                                                                                                          |
| Cable entry                                              | 3 entries tapped for M20 x 1.5                                                                                                                                                           |
| Electromagnet interlocking                               | Locking on energisation and unlocking on de-energisation of solenoid                                                                                                                     |
| [Us]&nbsp;solenoid&nbsp;rate&nbsp;of&nbsp;supply voltage | 24 V AC/DC                                                                                                                                                                               |
| Cable outer diameter                                     | 7...13 mm                                                                                                                                                                                |
| Electrical connection                                    | Spring terminal, clamping capacity: 1 x 1.5 mm <sup>2</sup> flexible or solid cable<br>Spring terminal, clamping capacity: 2 x 0.5 mm <sup>2</sup> flexible cables with 13 mm bared ends |
| Number of poles                                          | 2                                                                                                                                                                                        |
| Locking options description                              | With interlocking, locking by solenoid                                                                                                                                                   |
| Local signalling                                         | 1 LED (orange) for actuator withdrawn<br>1 LED (green) for actuator inserted and locked                                                                                                  |
| Signalling circuit voltage                               | 24 V                                                                                                                                                                                     |

## Complementary

|                                              |                                                                                                                           |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Insulation                                   | Double insulated                                                                                                          |
| Positive opening                             | With NC contact                                                                                                           |
| Supply voltage type                          | AC/DC                                                                                                                     |
| Supply frequency                             | 50/60 Hz                                                                                                                  |
| Load factor                                  | 1                                                                                                                         |
| Signalling circuit type                      | AC/DC                                                                                                                     |
| Mechanical durability                        | 1000000 cycles                                                                                                            |
| Minimum actuation speed                      | 0.01 m/s                                                                                                                  |
| Maximum actuation speed                      | 0.5 m/s                                                                                                                   |
| [Ie] rated operational current               | 0.55 A at 24 V, DC-13, R300 conforming to IEC 60947-5-1<br>0.75 A at 240 V, AC-15, C300 conforming to IEC 60947-5-1       |
| [Ithe] conventional enclosed thermal current | 4 A                                                                                                                       |
| Maximum load current                         | <= 15 A                                                                                                                   |
| [Ui] rated insulation voltage                | 300 V conforming to UL 508<br>300 V conforming to CSA C22.2 No 14<br>250 V (pollution degree 3) conforming to IEC 60947-1 |
| [Uimp] rated impulse withstand voltage       | 4 kV conforming to IEC 60947-5-1                                                                                          |
| Minimum switching current                    | 10 mA at 20 °C                                                                                                            |
| Minimum switching voltage                    | 17 V                                                                                                                      |

|                                          |                                                                                                                                                                                                                                                               |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Short-circuit protection                 | 4 A cartridge fuse type gG (gl)<br>6 A type fast blow                                                                                                                                                                                                         |
| Maximum actuator forcible withdrawal rtc | 1400 N                                                                                                                                                                                                                                                        |
| Minimum actuator force for extraction    | 20 N                                                                                                                                                                                                                                                          |
| Resistance to mechanical impact          | 1.2 J against the partition<br>4.9 J without partition                                                                                                                                                                                                        |
| Maximum operating rate                   | 10 cyc/mn for maximum durability                                                                                                                                                                                                                              |
| Safety level                             | Can reach category 4 with the appropriate monitoring system and correctly wired conforming to ISO 13849-1<br>Can reach PL = e with the appropriate monitoring system and correctly wired conforming to ISO 13849-1<br>Can reach SIL 3 conforming to IEC 61508 |
| Safety reliability data                  | B10d = 5500000 value given for a life time of 20 years limited by mechanical or contact wear                                                                                                                                                                  |
| Body material                            | PA (polyamide)                                                                                                                                                                                                                                                |
| Head material                            | PA (polyamide)                                                                                                                                                                                                                                                |
| Depth                                    | 51 mm                                                                                                                                                                                                                                                         |
| Height                                   | 205 mm                                                                                                                                                                                                                                                        |
| Width                                    | 44 mm                                                                                                                                                                                                                                                         |
| Net weight                               | 0.53 kg                                                                                                                                                                                                                                                       |

## Environment

|                                       |                                                                                                            |
|---------------------------------------|------------------------------------------------------------------------------------------------------------|
| Standards                             | IEC 60204-1<br>IEC 62061<br>IEC 60947-5-1<br>ISO 13849-1<br>UL 508<br>CSA C22.2 No 14<br>EN 1088/ISO 14119 |
| Product certifications                | UL[RETURN]CSA[RETURN]TÜV                                                                                   |
| Protective treatment                  | TC                                                                                                         |
| Ambient air temperature for operation | -25...60 °C                                                                                                |
| Ambient air temperature for storage   | -40...70 °C                                                                                                |
| Vibration resistance                  | 5 gn (f= 10...500 Hz) conforming to IEC 60068-2-6                                                          |
| Shock resistance                      | 10 gn for 11 ms conforming to IEC 60068-2-27                                                               |
| Electrical shock protection class     | Class II conforming to IEC 61140                                                                           |
| IP degree of protection               | IP66 conforming to EN/IEC 60529 and EN/IEC 60947-5-1<br>IP67                                               |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 6.35 cm  |
| Package 1 Width              | 25.4 cm  |
| Package 1 Length             | 7.62 cm  |
| Package 1 Weight             | 0.64 kg  |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 8        |
| Package 2 Height             | 15 cm    |
| Package 2 Width              | 30 cm    |
| Package 2 Length             | 40 cm    |
| Package 2 Weight             | 5.684 kg |
| Unit Type of Package 3       | PAL      |
| Number of Units in Package 3 | 128      |
| Package 3 Height             | 60 cm    |
| Package 3 Width              | 80 cm    |
| Package 3 Length             | 128 cm   |
| Package 3 Weight             | 100.8 kg |

## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| Circularity Profile                        | <a href="#">End of Life Information</a>                                                                                                                                                                                                                                                                                                                                           |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|