



# XCSR13M12

Miniature Safety RFID switch, unique pairing, Daisy-chain + EDM, 8-pin, M12 connector

COMMERCIALISED

## Main

|                           |                                   |
|---------------------------|-----------------------------------|
| Range of product          | Telemecanique Safety switches XCS |
| Product or component type | Preventa RFID safety switch       |
| Component name            | XCSR                              |

## Complementary

|                                |                                                                                |
|--------------------------------|--------------------------------------------------------------------------------|
| Design                         | Miniature                                                                      |
| Size                           | Switch: 42 x 28.5 x 18 mm actuator: 42 x 28.5 x 18 mm                          |
| Material                       | Plastic                                                                        |
| Electrical connection          | 1 male connector                                                               |
| Connector type                 | M12 male                                                                       |
| Type of output stage           | Solid-state, PNP                                                               |
| Safety outputs                 | 2 NO                                                                           |
| Local signalling               | Green, yellow and red 1 multi-colour LED                                       |
| [Ue] rated operational voltage | 24 V DC (– 20...20 %) SELV or PELV conforming to IEC 60204-1                   |
| Protection type                | Short-circuit protection                                                       |
| Switching capacity in mA       | 300 mA                                                                         |
| Switching frequency            | <= 0.5 Hz                                                                      |
| Response time                  | <55 ms +12 ms per switch in daisy-chain (Risk time according to IEC 60947-5-3) |
| Tightening torque              | 0.8...1.2 N.m                                                                  |
| Standards                      | IEC 60947-5-3<br>ISO 14119<br>IEC 60947-5-2                                    |
| Product certifications         | TÜV<br>Ecolab                                                                  |
| Marking                        | CE<br>UKCA                                                                     |

TÜV

|                                   |                                                                                                                                     |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Safety level                      | SIL 3 conforming to IEC 61508 SILCL 3 conforming to IEC 62061 PL = e conforming to ISO 13849-1 category 4 conforming to ISO 13849-1 |
| Safety reliability data           | PFHd = 2.62E-9 1/h conforming to IEC 62061 PFHd = 2.62E-9 1/h conforming to ISO 13849-1                                             |
| Vibration resistance              | +/- 1 mm (f= 10-55Hz) conforming to IEC 60068-2-6                                                                                   |
| Shock resistance                  | 30 gn for 11ms conforming to IEC 60068-2-27                                                                                         |
| Electrical shock protection class | Class III conforming to IEC 61140                                                                                                   |
| IP degree of protection           | IP65 conforming to IEC 60529 IP67 conforming to IEC 60529                                                                           |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TMSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Updated: 23/06/2025

