



### Main

Device short name	XCSTE
Enclosure type	Dust and damp proof enclosure for indoor/outdoor Corrosion resistance enclosure for indoor/outdoor

### Complementary

[In] rated current	6 A
[Us] rated supply voltage	120 V
Actuator	Key
Contact operation	Slow-break
Contacts type and composition	2 NC
Depth	33.02 mm
Electromagnet interlocking	Locking on energisation and unlocking on de-energisation of solenoid
Enclosure material	plastic enclosure
Height	93.22 mm
Locking options description	With interlocking, locking by solenoid With locking of actuator, unlocking by key operated lock
Number of poles	2
Permissible voltage	300 V AC

### Environment

Ambient air temperature for operation	-13...140 °F
IP degree of protection	IP67
NEMA degree of protection	NEMA 4/4X/12

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.064 cm
Package 1 Width	10.668 cm
Package 1 Length	11.684 cm
Package 1 Weight	439.989 g

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>