XE2NP2141

Limit switch contact block, Limit switches XC Standard, 2NC, slow break, simultaneous



Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch contact block
Device short name	XE2N
Associated body	ZCKJ7 ZCKS7 ZCKL7 ZCD27 ZCKJ7D ZCKM7 ZCP27
Number of poles	2
Contacts type and composition	2 NC
Contact operation	Slow-break, simultaneous

Complementary

Product compatibility	XCKP	
	XCKM	
	XCKJ	
	XCKD	
	XCKS	
	XCKL	
Electrical connection	Screw-clamp terminals, clamping capacity: 1 x 0.52 x 2.5 mm ²	
Contacts insulation form	Zb	
Contacts material	Silver plated contacts	
Positive opening	With	
Minimum actuation speed	6 m/min	
Contact code designation	A300, AC-15 (Ue = 240 V), Ie = 3 A, Ithe = 10 A conforming to IEC 60947-5-1	
	appendix A	
	Q300, DC-13 (Ue = 250 V), le = 0.27 A conforming to IEC 60947-5-1 appendix A	
Maximum resistance across terminals	25 mOhm conforming to IEC 60255-7 category 3	
[Ui] rated insulation voltage	300 V conforming to UL 508	
	500 V (pollution degree 3) conforming to IEC 60947-1	
	300 V conforming to CSA C22.2 No 14	
[Uimp] rated impulse withstand voltage	6 KV conforming to IEC 60664	
	6 kV conforming to IEC 60947-1	
Short-circuit protection	10 A cartridge fuse, type gG	
Electrical durability	5000000 Cycles, DC-13 120 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5	
	conforming to IEC 60947-5-1 appendix C	
	5000000 Cycles, DC-13 24 V, 13 W, operating rate <60 cyc/mn, load factor: 0.5	
	conforming to IEC 60947-5-1 appendix C	
	5000000 cycles, DC-13 48 V, 9 W, operating rate <60 cyc/mn, load factor: 0.5	
	conforming to IEC 60947-5-1 appendix C	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.500 cm	
Package 1 Width	2.300 cm	
Package 1 Length	4.500 cm	
Package 1 Weight	21.000 g	
Unit Type of Package 2	S01	

Number of Units in Package 2	50
Package 2 Height	15.000 cm
Package 2 Width	15.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	1.359 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------

