# XF9D251

Overtravel limit switches, XR and XF, power switch, manual reset, 4P, 50/25 A, 2/3P scheme



## Main

Range of product	XR and XF
Product or component type	Overtravel limit switches
Device short name	XF9
Electrical circuit type	Power circuit
Product specific application	Safety of hoisting equipment
Material	Aluminium alloy: case
Type of operator	Manual latching, restricted by a padlockable device
Number of poles	4
[le] rated operational current	, le = 50 A 2-pole scheme AC-3, le = 25 A 3-pole scheme

Complementary

Reset	Manual reset	
Switch actuation	Horizontal approach	
Maximum displacement angle	75 °	
Contacts type and composition	Without auxiliary contact block	
Contact operation	Snap action	
[Ithe] conventional enclosed thermal current	40 A at -2540 °C 3-pole scheme 80 A at -2540 °C 2-pole scheme	
[Ui] rated insulation voltage	500 V conforming to IEC 158-1 500 V conforming to IEC 947-4 500 V conforming to VDE 0110 group C 600 V conforming to CSA C22.2 No 14	
Rated breaking capacity	180 KA at 660 V 2-pole scheme conforming to IEC 158-1 400 kA at 500 V 2-pole scheme conforming to IEC 158-1	
Cable cross section	1 flexible cable 16 mm² 1 flexible cable 1.510 mm² without cable end 1 solid cable 1.56 mm² without cable end 2 flexible cable 14 mm² with cable end 2 flexible cable 1.56 mm² without cable end 2 solid cable 1.56 mm² without cable end	
Cable entry	2 entries tapped for Pg 21 cable gland	
Net weight	2.2 kg	

#### Environment

Standards	NF C 63-110	
	VDE 0660	
	IEC 158-1	
	IEC 947-1	
	IEC 947-4	
Product certifications	CSA	
Protective treatment	TC	
Ambient air temperature for operation	-2570 °C	
Ambient air temperature for storage	-4070 °C	
IP degree of protection	IP54 conforming to IEC 60529	

Pac	kin	a U	Ini	its
		9 ~	,	

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.200 cm
Package 1 Width	22.200 cm
Package 1 Length	27.400 cm
Package 1 Weight	2.646 kg
Unit Type of Package 2	S06
Number of Units in Package 2	18
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	60.556 kg

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

### Contractual warranty

Warranty	18 months