XGSZ09L2

Radio frequency identification XG, pre wired M12 female connector, cable 2 m, IP67



Main

IVICIII		
Range of product	Telemecanique Radio frequency identification XG	
Accessory / separate part categor	Connection accessories	
Accessory / separate part type	Connecting cable	
Accessory / separate part designation	Pre-wired M12 female connector	
Accessory / separate part destination	For 24 V DC supply of connection box	
Cable length	2 m	

Complementary

Product compatibility	TCSAMT31FP XGSZ33ETH	
Electrical connection	1 female connector M12 4 pins A coding	
Colour	Black	
Net weight	0.115 kg	

Environment

IP degree of protection	IP67
-------------------------	------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.000 cm
Package 1 Width	15.500 cm
Package 1 Length	17.500 cm
Package 1 Weight	85.900 g
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.792 kg

Offer Sustainability

Yes
WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
sustainability@tesensors.com

Contractual warranty

	· · · · · · · · · · · · · · · · · · ·
Warranty	18 months

Product data sheet Connections and Schema

XGSZ09L2

Wiring Diagram

Modbus Connections



Pin no.		Signal
1	Red	+ 24 VDC
2	NC	-
3	Black	0 VDC
4	NC	-