XGSZ12E1201

OsiSense XG cable M12/M12 D coded - Ethernet - 1m



Main

Range of product	Telemecanique Radio frequency identification XG
Accessory / separate part categor	Connection accessories
Accessory / separate part type	Connecting cable
Product or component type	Ethernet copper cable
Product compatibility	XGSZ33ETH XGSZ33EIP
Accessory / separate part destination	Ethernet network

Complementary

Cable length	1 m
Transmission rate	100 Mbit/s
Transmission support medium	2 twisted shielded pairs
Communication network category	5e
AWG gauge	AWG 26
Electrical connection	1 male connector, M12 straight connector with 4 pin(s) - encoding type: D coding 1 male connector, M12 straight connector with 4 pin(s)
Conductor material	Copper
Cover material	PUR
Net weight	0.075 kg

Environment

IP degree of protection	IP67	
Standards	ISO/IEC 11801 Ed.2, 2002	
	IEC 60754-1	
	EIA/TIA-568	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2 cm	
Package 1 Width	28 cm	
Package 1 Length	30 cm	
Package 1 Weight	80 g	

Offer Sustainability

For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Product data sheet Connections and Schema

XGSZ12E1201

Wiring Diagram

