

# XMEP060BD71F

Electronic pressure sensors, Pressure sensors XM, transmitter, XMEP, 60 bar, G1/4 A male, 0...10 V, M12, set of 1



## Main

|                           |                                                                                |
|---------------------------|--------------------------------------------------------------------------------|
| Range of product          | Telemecanique Pressure sensors XM                                              |
| Product or component type | Electronic pressure sensors                                                    |
| Pressure sensor type      | Pressure transmitter                                                           |
| Pressure sensor name      | XMEP                                                                           |
| Electrical circuit type   | Control circuit                                                                |
| Pressure rating           | 60 bar                                                                         |
| Local display             | Without                                                                        |
| Controlled fluid          | Fresh water (0...125 °C)<br>Air (-30...125 °C)<br>Hydraulic oil (-30...125 °C) |
| Fluid connection type     | G 1/4A (male) conforming to DIN 3852-E                                         |
| Electrical connection     | 1 male connector M12 4 pins                                                    |
| [Us] rated supply voltage | 24 V DC SELV (voltage limits: 12...36 V)                                       |
| Current consumption       | < 7 mA                                                                         |
| Type of output signal     | Analogue                                                                       |
| Analogue output function  | 0...10 V, 3-wire                                                               |
| Quantity per set          | Set of 1                                                                       |
| Type of packing           | Individual                                                                     |

## Complementary

|                                         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Pressure setting range                  | 0...60 bar                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Maximum permissible accidental pressure | 150 bar                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Destruction pressure                    | 300 bar                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Materials in contact with fluid         | Fluorocarbon FPM<br>Stainless steel AISI 316L                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Operating position                      | Any position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Protection type                         | Reverse polarity<br>Load short-circuit                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Electromagnetic compatibility           | Electrostatic discharge immunity test conforming to ISO 10605 criteria A 15 kV air, 15 kV contact<br>Susceptibility to electromagnetic fields conforming to ISO 11452-2 criteria A 100 V/m 200...2000 MHz<br>Susceptibility to electromagnetic fields conforming to ISO 11452-4 criteria A 100 mA 20...400 MHz<br>Susceptibility to conducted disturbances conforming to EN/IEC 61000-4-6 criteria A 30 V 0.15...80 MHz<br>Electrical fast transient/burst immunity test conforming to EN/IEC 61000-4-4 criteria A 4 kV<br>Susceptibility to conducted transient disturbances conforming to ISO 7637-2 criteria B level 3 |
| [Uimp] rated impulse withstand voltage  | 0.5 kV                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Response time on output                 | <= 2 ms 10...90 % of full scale                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Measurement accuracy                    | +/- 0.5 % of the measuring range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Resolution                              | 0.1 % of the measuring range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Drift of the sensitivity                | +/- 0.02 % of measuring range/°K                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Drift of the zero point                 | +/- 0.02 % of measuring range/°K                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Long term stability                     | +/- 0.5 % of the measuring range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Mechanical durability                   | 10000000 cycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|            |          |
|------------|----------|
| Net weight | 0.095 kg |
| Diameter   | 26 mm    |
| Length     | 38.1 mm  |

## Environment

|                                       |                                                                                                                                    |
|---------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| Standards                             | ISO 14982<br>EN/IEC 61326-2-3<br>UL 61010-1<br>EN 13309<br>ISO 13766<br>ECE 10R-5                                                  |
| Product certifications                | cULus[RETURN]CE[RETURN]E2                                                                                                          |
| Ambient air temperature for operation | -40...100 °C                                                                                                                       |
| Ambient air temperature for storage   | -50...100 °C                                                                                                                       |
| Vibration resistance                  | 12 gn sinus (f = 20...520 Hz) test 4 conforming to ISO 16750-3<br>18 gn random (f = 10...2000 Hz) test 4 conforming to ISO 16750-3 |
| Shock resistance                      | 50 gn for 11 ms conforming to EN/IEC 60068-2-27                                                                                    |
| IP degree of protection               | IP65 conforming to EN/IEC 60529<br>IP67 conforming to EN/IEC 60529<br>IP69K conforming to EN/IEC 60529                             |

## Packing Units


|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 4.1 cm |
| Package 1 Width              | 4.5 cm |
| Package 1 Length             | 8.5 cm |
| Package 1 Weight             | 95.0 g |

## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| Circularity Profile                        | No need of specific recycling operations                                                                                                                                                                                                                                                                                                                                          |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |

## Dimensions

mm  
in.




(1) SW24, tightening torque □ 24 N-m / 212 lb-in

---

## Connections and Schema

---

### Connector Wiring



(1) V out  
Pin Not connected  
2 :

---

Performance Curves

---

Curves

