XS1N30PB349SCTF

Inductive proximity sensors XS, inductive sensor XS1 M30, L, brass, Sn20mm, 12...24 VDC, M8



Main

| Range of product | Telemecanique Inductive proximity sensors XS |
|--|--|
| Series name | General purpose |
| Sensor type | Inductive proximity sensor |
| Sensor name | XS1 |
| Sensor design | Cylindrical M30 |
| Size | 43 mm |
| Body type | Fixed |
| Detector flush mounting acceptance | Flush mountable |
| Material | Metal |
| Enclosure material | Nickel plated brass |
| Type of output signal | Discrete |
| Wiring technique | 3-wire |
| [Sn] nominal sensing distance | 20 mm |
| | |
| Discrete output function | 1 NC |
| Discrete output function Output circuit type | 1 NC DC |
| | |
| Output circuit type | DC |
| Output circuit type Discrete output type | DC PNP |
| Output circuit type Discrete output type Electrical connection [Us] rated supply | DC PNP Cable |
| Output circuit type Discrete output type Electrical connection [Us] rated supply voltage Switching capacity in | DC PNP Cable 1224 V DC with reverse polarity protection <= 200 mA DC with overload and short-circuit |

Complementary

| Complementary | |
|------------------------|------------------------------|
| Thread type | M30 x 1.5 |
| Detection face | Frontal |
| Front material | PPS |
| Operating zone | 016 mm |
| Differential travel | 115% of Sr |
| Status LED | Output state: 1 LED (yellow) |
| Supply voltage limits | 1036 V DC |
| Switching frequency | <= 500 Hz |
| Maximum voltage drop | <2 V (closed) |
| Current consumption | 010 mA no-load |
| Maximum delay first up | 5 ms |
| Maximum delay response | 0.6 ms |
| Maximum delay recovery | 1.4 ms |
| Marking | CE |
| Threaded length | 32 mm |
| Height | 30 mm |
| Length | 43 mm |
| | |

Environment

| CSA[RETURN]UL |
|--|
| -4070 °C |
| 25 gn amplitude = +/- 2 mm (f = 1055 Hz) conforming to IEC 60068-2-6 |
| 50 gn for 11 ms conforming to IEC 60068-2-27 |
| |

Packing Units

| • | | |
|------------------------------|---------|--|
| Unit Type of Package 1 | PCE | |
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 4.5 cm | |
| Package 1 Width | 9 cm | |
| Package 1 Length | 14.8 cm | |
| Package 1 Weight | 0.2 kg | |
| | | |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|--|---|
| Circularity Profile | ☐ End of Life Information |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

