XS2M12PC410D

inductive sensor XS2 M12, 12..24VDC



Main

Range of product	Telemecanique Inductive proximity sensors XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Sensor name	XS2
Sensor design	Cylindrical M12
Size	66 mm
Body type	Fixed
Detector flush mounting acceptance	Non flush mountable
Material	Metal
Type of output signal	Discrete
Wiring technique	4-wire
Discrete output function	1 NO + 1 NC
Output circuit type	DC
Discrete output type	PNP
Electrical connection	Male connector M12, 4 pins
[Us] rated supply voltage	1224 V DC with reverse polarity protection
Switching capacity in mA	<= 200 mA with overload and short-circuit protection
IP degree of protection	IP68 double insulation conforming to IEC 60529

Complementary

Thread type	M12 x 1	
Detection face	Frontal	
Front material	PPS	
Enclosure material	Nickel plated brass	
Operating zone	03.2 mm	
Differential travel	115% of Sr	
Status LED	Output state: 1 LED (yellow)	
Supply voltage limits	1036 V DC	
Maximum voltage drop	<2 V (closed)	
Current consumption	010 mA no-load	
Maximum delay first up	5 ms	
Marking	CE	
Threaded length	42 mm	
Length	66 mm	

Environment

Product certifications	UL[RETURN]CSA
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4085 °C
Vibration resistance	25 gn amplitude = +/- 2 mm (f = 1055 Hz) conforming to IEC 60068-2-6
Shock resistance	50 gn for 11 ms conforming to IEC 60068-2-27

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.900 cm
Package 1 Width	7.600 cm
Package 1 Length	11.700 cm
Package 1 Weight	36.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	22
Package 2 Height	15 cm
Package 2 Width	15 cm
Package 2 Length	40 cm
Package 2 Weight	1.214 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Circularity Profile	[™] End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

