## XS4P18PB370E1

Inductive proximity sensors XS, inductive sensor XS4 M18, L62mm, PPS, Sn8mm, 12...48 VDC, cable 2 m



#### Main

| Range of product                   | Telemecanique Inductive proximity sensors XS            |
|------------------------------------|---------------------------------------------------------|
| Series name                        | General purpose                                         |
| Sensor type                        | Inductive proximity sensor                              |
| Sensor name                        | XS4                                                     |
| Sensor design                      | Cylindrical M18                                         |
| Size                               | 36 mm                                                   |
| Body type                          | Fixed                                                   |
| Detector flush mounting acceptance | Non flush mountable                                     |
| Material                           | Plastic                                                 |
| Type of output signal              | Discrete                                                |
| Wiring technique                   | 3-wire                                                  |
| [Sn] nominal sensing distance      | 8 mm                                                    |
| Discrete output function           | 1 NC                                                    |
| Output circuit type                | DC                                                      |
| Discrete output type               | PNP                                                     |
| [Us] rated supply voltage          | 1248 V DC with reverse polarity protection              |
| Switching capacity in mA           | <= 200 mA DC with overload and short-circuit protection |
| IP degree of protection            | IP68 double insulation conforming to IEC 60529          |
|                                    |                                                         |

#### Complementary

| Complementary          |                              |
|------------------------|------------------------------|
| Thread type            | M18 x 1                      |
| Detection face         | Frontal                      |
| Front material         | PPS                          |
| Enclosure material     | PPS                          |
| Operating zone         | 06.4 mm                      |
| Differential travel    | 115% of Sr                   |
| Status LED             | Output state: 1 LED (yellow) |
| Supply voltage limits  | 1058 V DC                    |
| Switching frequency    | <= 2000 Hz                   |
| Maximum voltage drop   | <2 V (closed)                |
| Current consumption    | 010 mA no-load               |
| Maximum delay first up | 10 ms                        |
| Maximum delay response | 0.15 ms                      |
| Maximum delay recovery | 0.35 ms                      |
| Marking                | CE                           |
| Threaded length        | 52 mm                        |
| Height                 | 18 mm                        |
| Length                 | 36 mm                        |
|                        |                              |

### Environment

| Product certifications                | CSA[RETURN]UL[RETURN]Ecolab[RETURN]CCC                               |
|---------------------------------------|----------------------------------------------------------------------|
| Ambient air temperature for operation | -2570 °C                                                             |
| Ambient air temperature for storage   | -4085 °C                                                             |
| Vibration resistance                  | 25 gn amplitude = +/- 2 mm (f = 1055 Hz) conforming to IEC 60068-2-6 |
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27                         |

### Packing Units

| Unit Type of Package 1       | PCE       |
|------------------------------|-----------|
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 5.200 cm  |
| Package 1 Width              | 8.200 cm  |
| Package 1 Length             | 20.000 cm |
| Package 1 Weight             | 176.000 g |
| Unit Type of Package 2       | S01       |
| Number of Units in Package 2 | 7         |
| Package 2 Height             | 15 cm     |
| Package 2 Width              | 15 cm     |
| Package 2 Length             | 40 cm     |
| Package 2 Weight             | 1.443 kg  |
|                              |           |

# Offer Sustainability

| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                 |
|--------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Circularity Profile                        | ☐ End of Life Information                                                                                                                                                                                                                                                                                                             |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com                                                                                                                                                                                                                                                                                                          |

