# XS4P30AB9D2

Inductive proximity sensors XS, inductive sensor XS4 M30, L53mm, PBT, Sn15mm, 12..24VDC, Cable 6m, Molex connector



#### Main

Range of product	Telemecanique Inductive proximity sensors XS
Series name	Application
Sensor type	Inductive proximity sensor
Electrical circuit type	Analog output
Sensor name	XS4
Sensor design	Cylindrical M30
Size	53 mm
Body type	Fixed
Detector flush mounting acceptance	Non flush mountable
Material	Plastic
Type of output signal	Analogue
Wiring technique	2-wire
[Sn] nominal sensing distance	15 mm
Output circuit type	DC
Analogue output range	420 mA
Electrical connection	1 remote connector Molex 4-pin
Cable length	6 m
[Us] rated supply voltage	1224 V DC
IP degree of protection	IP67 conforming to IEC 60529

#### Complementary

Complementary		
Thread type	M30 x 1.5	
Detection face	Frontal	
Front material	PPS	
Enclosure material	PBT	
Operating zone	1.515 mm	
Repeat accuracy	<= 3% of Sr	
Linearity error	+/- 2 mA	
Cable composition	3 x 0.34 mm²	
Wire insulation material	PVC	
Supply voltage limits	1038 V DC	
Switching frequency	<= 300 Hz	
Current consumption	4 mA no-load	
Maximum output current drift	10 %	
Marking	CE	
Threaded length	32 mm	
Height	30 mm	
Length	53 mm	

#### Environment

Product certifications	UL[RETURN]CSA
Ambient air temperature for operation	-2570 °C
Ambient air temperature for storage	-4085 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.0 cm
Package 1 Width	9.5 cm
Package 1 Length	13.0 cm
Package 1 Weight	231.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	30
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	7.318 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
Circularity Profile	☑ End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

### Contractual warranty

- Contraction to the contract of the contract		
Warranty	18 months	