XS612B1PBM12SAJ

Inductive proximity sensors XS, inductive sensor XS6 M12, L62mm, brass, Sn4mm, 12...48 VDC, M12



Main

| TTT CALL | |
|------------------------------------|--|
| Range of product | Telemecanique Inductive proximity sensors XS |
| Series name | General purpose |
| Sensor type | Inductive proximity sensor |
| Device application | Mobile equipment |
| Sensor name | XS6 |
| Sensor design | Cylindrical M12 |
| Size | 62 mm |
| Body type | Fixed |
| Detector flush mounting acceptance | Flush mountable |
| Material | Metal |
| Type of output signal | Discrete |
| Wiring technique | 3-wire |
| [Sn] nominal sensing distance | 4 mm |
| Discrete output function | 1 NC |
| Output circuit type | DC |
| Discrete output type | PNP |
| Electrical connection | Male connector M12, 4 pins |
| [Us] rated supply voltage | 1248 V DC with reverse polarity protection |
| Switching capacity in mA | <= 200 mA DC with overload and short-circuit protection |
| IP degree of protection | IP68 double insulation conforming to IEC 60529 IP69K conforming to DIN 40050 |
| | |

Complementary

| Complementary | | |
|------------------------|------------------------------|--|
| Thread type | M12 x 1 | |
| Detection face | Frontal | |
| Front material | PPS | |
| Enclosure material | Nickel plated brass | |
| Sensing range | > 2.54 mm | |
| Operating zone | 03.2 mm | |
| Differential travel | 115% of Sr | |
| Status LED | Output state: 1 LED (yellow) | |
| Supply voltage limits | 1058 V DC | |
| Switching frequency | <= 2500 Hz | |
| Maximum voltage drop | <2 V (closed) | |
| Current consumption | <= 10 mA no-load | |
| Maximum delay first up | 10 ms | |
| Maximum delay response | 0.2 ms | |
| Maximum delay recovery | 0.2 ms | |
| Marking | CE | |
| Threaded length | 42 mm | |
| Length | 62 mm | |
| Net weight | 0.02 kg | |
| | | |

Environment

| Product certifications | E2[RETURN]UL[RETURN]CSA | |
|---------------------------------------|--|--|
| Ambient air temperature for operation | -2570 °C | |
| Ambient air temperature for storage | -4085 °C | |
| Vibration resistance | 25 gn amplitude = +/- 2 mm (f = 1055 Hz) conforming to IEC 60068-2-6 | |
| Shock resistance | 50 gn for 11 ms conforming to IEC 60068-2-27 | |

Packing Units

| Unit Type of Package 1 | PCE | |
|------------------------------|--------|--|
| Number of Units in Package 1 | 1 | |
| Package 1 Height | 4.2 cm | |
| Package 1 Width | 9.6 cm | |
| Package 1 Length | 6.6 cm | |
| Package 1 Weight | 40 g | |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|--|--|--|
| Circularity Profile | [™] End of Life Information | |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisonony phthalate (DINP), which is known to the State of California to cause cancer and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go www.P65Warnings.ca.gov | |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com | |

