

# XS8T2PC440LD

inductive sensor XS8 26x26x26 - plastic -  
Sn15mm - 12..48VDC - M12



## Main

Range of product	Telemecanique Inductive proximity sensors XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Product specific application	-
Sensor name	XS8
Sensor design	Cubic form 26 x 26 x 26
Size	26 mm
Body type	Fixed
Detector flush mounting acceptance	Non flush mountable
Material	Plastic
Enclosure material	Plastic
Type of output signal	Discrete
Wiring technique	4-wire
[Sn] nominal sensing distance	15 mm
Discrete output function	1 NO + 1 NC
Output circuit type	DC
Discrete output type	PNP
Electrical connection	Remote male connector M12, 4 pins
Cable length	0.8 m
[Us] rated supply voltage	12...48 V DC
Switching capacity in mA	<= 200 mA
IP degree of protection	IP67

## Complementary

Detection face	5 positions turret head
Front material	Plastic
Switching frequency	<= 500 Hz
Marking	CE
Depth	26 mm
Height	26 mm
Width	26 mm

## Environment

Product certifications	UL[RETURN]CSA[RETURN]CCC
Ambient air temperature for operation	-25...70 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.2 cm
Package 1 Width	8 cm
Package 1 Length	12.5 cm
Package 1 Weight	136 g

## Offer Sustainability

---

Sustainable offer status	Green Premium product
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

---

## Contractual warranty

---

Warranty	18 months
----------	-----------

---