Product data sheet Characteristics

XU5M18PP9A4L5

Photoelectric sensors XU, XU5, 10…30 V, 500 Hz, DC



Main

Main	
Range of product	Telemecanique Photoelectric sensors XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor
Sensor name	XU5
Sensor design	Cylindrical M18
Detection system	Diffuse
Material	Stainless steel
Type of output signal	Discrete
Supply circuit type	DC
Wiring technique	3-wire
Discrete output type	PNP
Discrete output function	1 NO or 1 NC programmable
Electrical connection	Cable
Cable length	5 m
Emission	Infrared diffuse
[Sn] nominal sensing distance	1.2 m diffuse

Complementary

Completition		
Enclosure material	Stainless steel : 304 CU	
Lens material	РММА	
Maximum sensing distance	0.15 m	
Output type	Solid state	
Supply voltage limits	1030 V DC	
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)	
Switching frequency	<= 500 Hz	
Maximum voltage drop	<1.5 V (closed state)	
Current consumption	<= 30 mA no-load	
Maximum delay first up	15 ms	
Maximum delay response	1 ms	
Maximum delay recovery	1 ms	
Setting-up	Sensitivity adjustment	
Diameter	18 mm	
Length	62 mm	

Environment

Product certifications	CSA[RETURN]CE[RETURN]UL
Ambient air temperature for operation	-2555 °C
Ambient air temperature for storage	-4070 °C
Vibration resistance	7 gn, amplitude = +/- 1.5 mm (f = 1055 Hz) conforming to IEC 60068-2-6
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP67 conforming to IEC 60529



Packing Units

J	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	9.5 cm
Package 1 Length	13.5 cm
Package 1 Weight	237.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	22
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	5.639 kg

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

