

XUC2ARCTL2

Photoelectric sensors XU, XUC, thru beam, Sn
50 m, 24...240VAC/DC, cable 2 m



Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	General purpose single mode
Electronic sensor type	Photo-electric sensor
Sensor name	XUC
Sensor design	Compact
Detection system	Thru beam
Material	Plastic
Type of output signal	Discrete
Supply circuit type	AC/DC
Wiring technique	5-wire
Discrete output function	1 C/O
Electrical connection	Cable
Cable length	2 m
Product specific application	-
Emission	Infrared thru beam
[Sn] nominal sensing distance	50 m thru beam

Complementary

Enclosure material	PC
Lens material	PMMA
Maximum sensing distance	60 m
Output type	Relay
Output function governance	Light or dark programmable
Add on output	Without
Cable composition	5 x 0.34 mm ²
Wire insulation material	PvR
Cable outer diameter	6 mm
Status LED	1 LED (yellow) for output state 1 LED (red) for stability
[Us] rated supply voltage	24...240 V AC/DC
Supply voltage limits	20...264 V AC
Output voltage	<= 250 V AC
Switching capacity in mA	3 A (cos φ = 1 for 0.5 million cycles at 1 operating cycle per second at 250 V)
Switching frequency	<= 20 Hz
Maximum power consumption in W	2 W
Time delay range	0...15 s monostable, on-delay or off-delay (programmable) delay
Maximum delay first up	60 ms
Maximum delay response	25 ms
Maximum delay recovery	25 ms
Setting-up	Sensitivity adjustment with potentiometer
Electrical durability	500000 cycles, switching capacity: 3000 mA, cos f = 1, operating rate <60 cyc/mn at 250 V
Depth	44 mm
Height	112 mm
Width	45 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Net weight	0.4 kg
Kit composition	Transmitter + receiver

Environment

Product certifications	CSA[RETURN]CE[RETURN]UL
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C
Vibration resistance	7 gn (f = 10...55 Hz) conforming to IEC 60068-2-6
Shock resistance	20 gn (duration = 11 ms) conforming to IEC 60068-2-27
IP degree of protection	IP67 conforming to IEC 60529
NEMA degree of protection	NEMA 12 conforming to IEC 60529 NEMA 13 conforming to IEC 60529 NEMA 3 conforming to IEC 60529 NEMA 4 conforming to IEC 60529 NEMA 4X conforming to IEC 60529 NEMA 6 conforming to IEC 60529 NEMA 6P conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months
----------	-----------