

XUE5AA2NM12

Photoelectric sensors XU, XUE, BGS,
measurement, Sn 6 m, 24 VDC, M12



Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	Application material handling
Electronic sensor type	Photo-electric sensor
Sensor name	XUE
Sensor design	Compact 90 x 90
Detection system	Diffuse
Material	Plastic
Supply circuit type	DC
Wiring technique	5-wire
Discrete output type	PNP
Discrete output function	2 NO/NC programmable
Analogue output range	4...20 mA
Electrical connection	1 male connector M12, 5 pins
Product specific application	Distance measurement on object
Emission	Infrared laser, pulsed, wavelength: 905 nm - class 1 conforming to IEC 600825-1 Red laser, pulsed, wavelength: 670 nm - class 2 conforming to IEC 600825-1
[Sn] nominal sensing distance	6 m

Complementary

Enclosure material	ABS, anti-shock
Lens material	PMMA
Linearity	<= +/- 40 mm
Spot dimension	4 x 12 mm at 6 meters
Status LED	Supply on: 1 LED (green) Output: 2 LEDs (yellow) Parametering: 4 LEDs (red) Slow mode: 1 LED (orange)
[Us] rated supply voltage	24 V DC with reverse polarity protection
Supply voltage limits	18...30 V DC
Switching capacity in mA	100 mA (overload and short-circuit protection)
Switching time	13 ms at fast mode 80 ms at slow mode
Maximum voltage drop	<2.4 V (closed state)
Current consumption	125 mA no-load
Maximum delay first up	80 Ms 13 ms
Maximum delay response	13 Ms fast mode 80 ms slow mode
Setting-up	Parametering by buttons
Height	93 mm
Length	95 mm
Width	42 mm
Net weight	0.2 kg

Environment

Product certifications	CE[RETURN]cULus
Ambient air temperature for operation	-10...50 °C
Ambient air temperature for storage	-40...80 °C
Vibration resistance	7 gn, amplitude = +/- 0.5 mm (f = 10...55 Hz) conforming to IEC 60947-5-2
Shock resistance	30 gn (duration = 11 ms) conforming to IEC 60947-5-2
IP degree of protection	IP67 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	16 cm
Package 1 Length	23 cm
Package 1 Weight	342 g


Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty


Warranty	18 months
----------	-----------

Dimensions



- (1) Receiver optical axis
(2) Transmitter optical axis


Dimensions with Fixing Bracket XUZA618



- (1) Optical axis


Wiring Schemes

M12 Connector



- 1 : + U_B
- 2 : Q_B
- 3 : - U_B
- 4 : Q_A
- 5 : 4...20mA


Output



- BN : Brown
- WH : White
- BU : Blue
- BK : Black
- GY : Grey

Curves


Minimum Size of Detectable Object Related to Distance



(y) Length of object (mm)
(x) Distance (m)

Curves

Light Spot Size (Not Visible)



a (m)	b (mm)	c (mm)
0	10	5
2	7	4
4	10	3
6	12	4