

XUM2BKCNL2T

photo-electric sensor - XUM - emitter -
12..24VDC - cable 2m

Main

Range of product	Telemecanique Photoelectric sensors XU
Series name	Application assembly
Electronic sensor type	Photo-electric sensor transmitter
Sensor name	XUM
Sensor design	Miniature
Detection system	Thru beam
Material	Metal
Supply circuit type	DC
Electrical connection	Cable
Cable length	2 m
Product specific application	-
Emission	Infrared thru beam
[Sn] nominal sensing distance	15 m need a receiver

Complementary

Enclosure material	Zamak and stainless steel
Lens material	Glass
Wire insulation material	PVC
Status LED	Stability: 1 LED (green) Transmitter: 1 LED (orange) Receiver/supply on: 1 LED (red/green)
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Supply voltage limits	10...30 V DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Switching frequency	1000 Hz
Maximum voltage drop	<3 V (closed state)
Current consumption	11 mA
Maximum delay first up	100 ms
Maximum delay response	0.5 ms
Maximum delay recovery	0.5 ms
Net weight	0.128 kg

Environment

Product certifications	cULus[RETURN]CE[RETURN]CTick
Ambient air temperature for operation	-40...70 °C
Ambient air temperature for storage	-30...60 °C
Vibration resistance	+/- 1.5 mm (f = 10...55 Hz)2 hours in each direction X, Y and Z conforming to IEC 60068-2-6
Shock resistance	500 m/s ² for 10 x in each direction X, Y and Z conforming to IEC 60068-2-27
IP degree of protection	IP65 conforming to IEC 60529 IP67 conforming to IEC 60529 IP69K conforming to DIN 40050

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty

18 months
