

# XUSLDSQ6A0280T

safety light curtains segments transmitter type  
4 - for finger protection-280 mm

## Main

|                                       |                                                   |
|---------------------------------------|---------------------------------------------------|
| Range of product                      | Telemecanique Safety light curtains XUSL          |
| Product or component type             | Safety light curtains segments transmitter type 4 |
| Device short name                     | XUSLDS                                            |
| Product compatibility                 | XUSLDM                                            |
| Product specific application          | For finger protection                             |
| Minimum object diameter for detection | 14 mm                                             |
| Height protected                      | 280 mm                                            |
| Number of beams                       | 24                                                |

## Complementary

|                           |                                                                   |
|---------------------------|-------------------------------------------------------------------|
| Detection system          | Transmitter-receiver system                                       |
| Response time             | 23 ms four segments<br>23 ms three segments<br>23 ms two segments |
| [Us] rated supply voltage | 24 V DC (+/- 20 %)against reverse polarity                        |
| Electrical connection     | Flying lead with 1 female connector M12, 4 pins                   |

## Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.