

XUSLDSY5A1560

safety light curtain segments type 4 - XUSLDS
- for hand protection - 1560 mm



Main

Range of product	Telemecanique Safety light curtains XUSL
Series name	Advanced
Product or component type	Safety light curtain segments type 4
Device short name	XUSLDS
Product specific application	For hand protection
Minimum object diameter for detection	30 mm
Height protected	1560 mm
Number of beams	78

Complementary

Product compatibility	XUSLDM
Detection system	Transmitter-receiver system
Response time	32 ms four segments 32 ms three segments 32 ms two segments
Kit composition	1 receiver(s) 1 transmitter(s) 2 sets of 2 brackets with fixings
Electrical connection	Flying lead with 1 female connector M12 4 pins receiver Flying lead with 1 female connector M12 4 pins transmitter
Net weight	7.5 kg

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.