

# XUSLDSY5A2120T

safety light curtains segments transmitter type  
4 -for hand protection - 2120 mm

## Main

|                                       |                                                   |
|---------------------------------------|---------------------------------------------------|
| Range of product                      | Telemecanique Safety light curtains XUSL          |
| Product or component type             | Safety light curtains segments transmitter type 4 |
| Device short name                     | XUSLDS                                            |
| Product compatibility                 | XUSLDM                                            |
| Product specific application          | For hand protection                               |
| Minimum object diameter for detection | 30 mm                                             |
| Height protected                      | 2120 mm                                           |
| Number of beams                       | 106                                               |

## Complementary

|                           |                                                                   |
|---------------------------|-------------------------------------------------------------------|
| Detection system          | Transmitter-receiver system                                       |
| Response time             | 32 ms four segments<br>32 ms three segments<br>32 ms two segments |
| [Us] rated supply voltage | 24 V DC (+/- 20 %)against reverse polarity                        |
| Electrical connection     | Flying lead with 1 female connector M12, 4 pins                   |

## Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|