



Main

Range of product	Telemecanique Safety light curtains XUSL
Accessory / separate part designation	IP67 protection tube
Accessory / separate part type	Protection tube
Accessory / separate part categor	Protection accessories
Product compatibility	XUSLB...1045 XUSLDS....1045 XUSLDM...1045
Accessory / separate part destination	Safety light curtain type 4
Quantity per set	Set of 2

Complementary

Material	Acrylic
Sensing distance reduction coefficient	0.90 Sn

Environment

IP degree of protection	IP67 conforming to IEC 60529
Resistance to chemical agents	Limited resistant against chlorinated or aromatic hydrocarbons Limited resistant against ketones Resistant aqueous solutions Resistant to inorganic diluted acids Resistant alkalis Limited resistant against esters Resistant aliphatic hydrocarbons Resistant detergents and cleaners
Environmental characteristic	UV resistant Humidity resistant Resistant against immersion in water Adverse weather resistant
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-25...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.