



## Main

|                                       |                                                |
|---------------------------------------|------------------------------------------------|
| Range of product                      | Telemecanique Safety light curtains XUSL       |
| Accessory / separate part designation | IP67 protection tube                           |
| Accessory / separate part type        | Protection tube                                |
| Accessory / separate part categor     | Protection accessories                         |
| Product compatibility                 | XUSLDS...0720<br>XUSLDM...0720<br>XUSLB...0720 |
| Accessory / separate part destination | Safety light curtain type 4                    |
| Quantity per set                      | Set of 2                                       |

## Complementary

|                                        |         |
|----------------------------------------|---------|
| Height                                 | 724 mm  |
| Material                               | Acrylic |
| Sensing distance reduction coefficient | 0.90 Sn |
| Net weight                             | 4.35 kg |

## Environment

|                                       |                                                                                                                                                                                                                                                                                                              |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection               | IP67 conforming to IEC 60529                                                                                                                                                                                                                                                                                 |
| Resistance to chemical agents         | Resistant to inorganic diluted acids<br>Resistant detergents and cleaners<br>Limited resistant against esters<br>Resistant aliphatic hydrocarbons<br>Limited resistant against ketones<br>Resistant alkalis<br>Limited resistant against chlorinated or aromatic hydrocarbons<br>Resistant aqueous solutions |
| Environmental characteristic          | Humidity resistant<br>Resistant against immersion in water<br>Adverse weather resistant<br>UV resistant                                                                                                                                                                                                      |
| Ambient air temperature for operation | 0...40 °C                                                                                                                                                                                                                                                                                                    |
| Ambient air temperature for storage   | -25...70 °C                                                                                                                                                                                                                                                                                                  |

## Packing Units

|                              |     |
|------------------------------|-----|
| Unit Type of Package 1       | PCE |
| Number of Units in Package 1 | 1   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|